



## Model N50

### FRONTAL DISHWASHER WITH DOUBLE SKIN CABINET

Specially designed stainless steel, indented anti-clog wash arms, easily removed for cleaning, without tools • Pressed molded wash tank with radial corners and double filters for hygiene and easy maintenance • Insulated double skin cabinet construction reduces energy costs, noise levels and keeps the wash area ambient temperature, to an absolute minimum (62 dBA) • 35 cm wash height is suitable for washing trays and big pizza dishes • Balanced door for a comfort use • Peristaltic rinse aid dosing

## Technical Characteristics



Dishwasher (Art.-Nr. 200707)		N50		
	(sec.)	Baskets/h	Dishes/h	Glasses/h
Electro mechanic control panel				
Wash cycle I *	120	30	540	1.080
Wash cycle II *	180	20	360	720
Dimensions (W x D x H)		605 x 605 x 850 mm		
Clear entry height		350 mm		
Basket size		500 x 500 mm		
Wash pump power		0,6 kW		
Tank element / boiler element		2 kW / 4,5 kW		
Total power / Voltage		5,1 kW - 400 Volt 3/N/PE 50 Hz		
Water supply temperature / water supply pressure / hardness water		max. 55°C / 200 - 400 kPa / min. 7 max. 12° F **		
Inlet water connection / drain / max. h drain		R 3/4" / 1" 3/4 / 65 mm		
Wash temperature / Rinse temperature		55° C / 85° C		
Tank capacity / Boiler capacity / Water consumption per cycle		12 l / 5,5 l / 2,5 l		
Pump capacity		287 l/min		
<b>Features and accessories</b>				
Double wash tank filters		●		
Pressed molded wash tank with radial corners		●		
Powerful anti-clog wash arms and contra-rotating light weight rinse arms		●		
Peristaltic rinse aid dosing		●		
Water supply pipe, drain pipe, main power cable		●		
Micro switch door		●		
Double skin cabinet		●		
Balanced door		●		
Rinse booster pump (PR)		○		
Drain pump (PS)		○		
Internal water softener (A) ( max. 20° dF )		○		
Detergent dosing (PD)		○		
Break tank (B)		○		
Salt low warning lamp		○		
Digital control panel ( Tronic )		○		
Equipment		1 universal, 2 of 18 dishes, 1 teaspoon rack		

\* theoretical production with water supply at 50° C

\*\* above 12° F we suggest a water softener

● = standard ○ = on demand



Cod. 901618 x 1



Cod. 901616 x 2



Cod. 901621 x 1

**SILANOS s.r.l.**  
 Via Grandi, 19  
 I-20096 Pioltello (Milano) ITALY  
 Telefono +39 029291161  
 Telefax +39 029267306  
 E-mail info@silanos.it  
 Internet www.silanos.it  
 TVA 02017050960