



## Model LP57E

### POT WASHER WITH DOUBLE SKIN CABINET

Specially designed stainless steel, indented anti-clog wash arms, easily removed for cleaning, without tools • Pressed molded wash tank with radial corners and double filters for hygiene and easy maintenance • Insulated double skin cabinet construction reduces energy costs, noise levels and keeps the wash area ambient temperature, to an absolute minimum • Large 570x620 mm basket with 620 mm wash height suitable for washing trays, gastronorm containers GN1/1 530x325 mm, bakery trays 600x400 mm, baskets, etc • Rinse booster pump • High efficiency, self draining wash pump for greater hygiene and ultimate washing power • Peristaltic rinse aid dosing

## Technical Characteristics



### Pot Washer (Art.-Nr. 206700)

### LP57E

	(sec.)	Baskets/h	Trays/h
Digital control panel with display temperatures and functions			
Wash cycle I *	75	48	432
Wash cycle II *	120	30	270
Wash cycle III *	180	20	180
Wash cycle IV * (on going)	600	6	54
Dimensions (W x D x H closed hood / open hood)	685 x 720 x 1.670 / 1840 mm		
Clear entry height	620 mm		
Basket size	570 x 620 mm		
Wash pump power	1,42 kW		
Tank element / boiler element * load switching	3 kW / 6 kW		
Total power / Voltage *	7,42 kW / 400 Volt 3-N-PE 50 Hz		
Water supply temperature / water supply pressure / hardness water	max. 55°C / 200 - 400 kPa / min. 7 max. 12° F **		
Inlet water connection / drain / max. h drain	R ¾" / 1" ¾ / 340 mm		
Wash temperature / Rinse temperature	55°C / 85° C		
Tank capacity / Boiler capacity / Water consumption per cycle	35 l / 9 l / 3 l		
Pump capacity	644 l/min		

### Features and accessories

Auto-self draining wash pump	●
Double wash tank filters	●
Pressed molded wash tank with radial corners	●
Powerful anti-clog wash arms and contra-rotating light weight rinse arms	●
Peristaltic rinse aid dosing	●
Water supply pipe, drain pipe, main power cable	●
Door auto-start micro switch	●
Double skin cabinet	●
Rinse booster pump (PR)	●
Digital control panel with display temperatures ( Tronic )	●
Drain pump (PS)	○
Internal water softener (A) ( max. 20°dF )	○
Detergent dosing (PD)	○
Break tank (B)	○
Salt low warning lamp	○
Steam condenser unit and heat recovery (CVC)	○
Equipment	1 universal, 1 of 9 trays

\* theoretical production & power with water supply at 50°C \*\* above 12° F we suggest a water softener

● = standard ○ = on demand

### SILANOS s.r.l.

Via Grandi, 19  
 I-20096 Pogliano (Milano) ITALY  
 Telefono +39 029291161  
 Telefax +39 029267306  
 E-mail info@silanos.it  
 Internet www.silanos.it  
 TVA 02017050960