

Model NS9000

FLIGHT CONVEYOR DISHWASHER



Panoramic, counterbalanced inspection doors for safe and easy access • Constructed entirely in stainless steel grade Aisi 304 • Insulated double skin cabinet construction reduces energy costs, noise and heat emissions • Specially designed stainless steel, indented anti-clog wash and rinse arms, easily removed for cleaning, without tools • Pressed molded tanks with radial corners and double filters for easy maintenance • High efficiency, self draining pumps for greater hygiene and ultimate washing power • Insulated rinse boiler • Electrical control impulses are rated at 24V to ensure complete levels of safety • Automatic start activates the pumps when there are dishes in the washing area • Double rinse module combines a pre-rinse and a final rinse with a pump and a tank heater element, boiler final rinse water is recirculated into the pre-rinse tank • Rinse economy device, for saving water and energy

Technical Characteristics



Conveyor dishwasher (Art.-Nr. 600605 DXE / 600606 SXE)	NS9000
Electromechanic control panel with thermoregulatory display	Dishes/h
Conveyor speed I * (variable-speed motor)	5.900
Conveyor speed II *(variable-speed motor)	8.860
Dimensions (W x D x H)	8.800 x 905 x 1.725 mm
Clear wash capacity (W x H)	630x460 mm
Zones	Pre-wash / 4xWash / Neutral Zone / Double Rinse
Prewash pump / Wash pump / 1° rinse pump	1,35 kW / 4x2 kW / 0,30 kW
Wash tank element / 1° Rinse tank / Boiler element	4x12 kW / 6 kW / 27 kW
Total power / Voltage	91 kW / 400 Volt 3-N-PE 50 Hz
Water supply temperature / water supply pressure / hardness water	max. 55°C / 200 - 400 kPa / min. 7 max. 12° F **
Inlet water connection / drain / max. h drain	R ¾" / 1" ¾" / floor drain
Prewash temperature / Wash temperature / Rinse temperature	40°C / 55°C / 85° C
Prewash tank capacity / Wash tank / 1° Rinse tank capacity	70 l / 4x100 l / 20 l
Prewash pump capacity / wash pump capacity	503 l/min / 644 l/min
Water consumption	480 l/h

Features and Accessoires

Auto-self draining pumps	●
Double rinse with rinse booster pump	●
Pressed molded tanks with radial corners and smooth surfaces	●
Double skin cabinet	●
Automatic start	●
Rinse economy device	●
Insulated rinse boiler	●
Lateral wash arms	●
Electrical control rated at 24 Volts	●
Length of loading zone 1.000 mm + 400 mm splash guard	●
Length of unloading zone 1.800 mm + 400 mm splash guard	●
Length of neutral zone 400 mm without inspection door	●
Length of pre-wash zone 600 mm with double deep filter system	●
Zone de séchage 12 kW allonge la machine de 400 mm – moteur 0,75kW	○
Zone de séchage 18 kW allonge la machine de 400 mm – moteur 0,75kW	○
Zone de séchage 18kW avec porte allonge de 500 mm – moteur 1,1kW	○
Steam condenser unit	○
Heat recovery system with heat pump +600 mm length	○
Length of neutral zone 600 mm with inspection door	○
Length of triple rinse zone 900 mm	○
Break tank (B) with pressure pump and atmospheric boiler	○
Conveyor belt for thermic trays	○

* theoretical production with water supply at 50° C

** above 12° F we suggest a water softener

● = standard ○ = on demand

SILANOS s.r.l.

Via Grandi, 19
 I-20096 Pioltello (Milano) ITALY
 Telefono +39 029291161
 Telefax +39 029267306
 E-mail info@silanos.it
 Internet www.silanos.it
 TVA 02017050960