



## STANDARD FEATURES



Control panel	ELECTROMECHANICAL
Wash arm	1 - Stainless steel
Rinse arm	2 - PP
Detergent injector	Optional
Rinse aid injector	Standard
Peristaltic rinse aid injector	Optional
Break tank	-
Water softener	Optional
Drain pump	Optional
Diagnose Wi-Fi	-

## TECHNICAL FEATURES

External size	415x465x595	LxPxH	[mm]
Overall size	710	DOA	[mm]
Clearance	220	A	[mm]
Maximum height for crockery	205	Au	[mm]
Rack size	350x350		[mm]
Tank size	11		[lt]
Rinse water consumption	2,4		[lt]
Wash pump	0,17		[kW]
Tank heater element	1,6		[kW]
Booster heater element	2,6		[kW]
Installed load	2,8		[kW]
Cycles	120		[sec]
Output cycles per hour	30		[cycle/h]
Electrical supply	230V/50Hz		
Noise	48		[dBA]
Weight	25		[kg]

Theoretical data with water supply at 55°C  
 Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C  
 Dimension depending on the type of basket used.



## STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent for rinse product  
1 universal basket, 1 cutlery rack

## GENERAL FEATURES

- Single-skinned cabinet with double-skinned door.
- Tank and door made of stainless steel AISI 304.
- Monobloc wash pump fixed directly to the tank.
- Easy-clean-dual-filter system.
- Stainless-steel wash arm and two rinse arms of composite material, all independent and rotary.
- Integral rinse aid dosing unit.
- Electromechanical control panel.

## PERFORMANCES

Supply water temperature	55°C nom.	15	20	25	30	35	40	45	50	55	60	[°C]
Maximum cycles feasible in continuous operation	<b>27</b>	24	25	27	27	27	27	27	27	27	27	[rack/h]
Total spending power from single-skin machine	<b>2,42</b>	2,75	2,75	2,75	2,75	2,75	2,87	2,58	2,50	2,42	2,33	[kW]
Total spending power from double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Sensible heat emitted into the room from single-skinned machine	<b>0,60</b>	0,61	0,60	0,60	0,60	0,60	0,60	0,60	0,60	0,60	0,60	[kW]
Sensible heat emitted into the room from double-skinned machine	-	-	-	-	-	-	-	-	-	-	-	[kW]
Latent heat emitted into the room	<b>0,28</b>	0,09	0,11	0,14	0,15	0,17	0,20	0,22	0,25	0,28	0,31	[kW]
Emitted standby power with closed door in single-skin machine	<b>0,29</b>	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	0,29	[kW]
Emitted standby power with closed door in double-skin machine	-	-	-	-	-	-	-	-	-	-	-	[kW]