



## STANDARD FEATURES



|                                | ELECTROMECHANICAL   |
|--------------------------------|---------------------|
| Control panel                  |                     |
| Wash arm                       | 2 - Stainless steel |
| Rinse arm                      | 2 - PP              |
| Detergent injector             | Optional            |
| Rinse aid hydraulic injector   | Standard            |
| Peristaltic rinse aid injector | Optional            |
| Break tank                     | -                   |
| Water softener                 | Optional            |
| Drain pump                     | Optional            |
| Diagnose Wi-Fi                 | -                   |

## TECHNICAL FEATURES

|                             |             |       |           |
|-----------------------------|-------------|-------|-----------|
| External size               | 465x510x695 | LxPxH | [mm]      |
| Overall size                | 855         | DOA   | [mm]      |
| Clearance                   | 295         | A     | [mm]      |
| Maximum height for crockery | 280         | Au    | [mm]      |
| Rack size                   | 400x400     |       | [mm]      |
| Tank size                   | 12          |       | [lt]      |
| Rinse water consumption     | 2,4         |       | [lt]      |
| Wash pump                   | 0,27        |       | [kW]      |
| Tank heater element         | 1,6         |       | [kW]      |
| Booster heater element      | 2,8         |       | [kW]      |
| Installed load              | 3,1         |       | [kW]      |
| Cycles                      | 120         |       | [sec]     |
| Output cycles per hour      | 30          |       | [cycle/h] |
| Electrical supply           | 230V/50Hz   |       |           |
| Noise                       | 48          |       | [dBA]     |
| Weight                      | 31          |       | [kg]      |

Theoretical data with water supply at 55°C

Where water hardness exceeds 8,43°e, a water softener is required. Not suitable for hot water over 30°C

Dimension depending on the type of basket used.



## STANDARD EQUIPMENT

Hoses (1 for each): Water connection, drain, transparent for rinse product  
1 universal basket, 1 cutlery rack

## GENERAL FEATURES

- Single-skinned cabinet with double-skinned door.
- Tank and door made of stainless steel AISI 304.
- Monobloc wash pump fixed directly to the tank.
- Easy-clean-dual-filter system.
- Two stainless-steel wash arm and two rinse arms of composite material, all independent and rotary.
- Integral rinse aid dosing unit.
- Electromechanical control panel.

## PERFORMANCES

|   | 55°C<br>nom. | 15   | 20   | 25   | 30   | 35   | 40   | 45   | 50   | 55   | 60   | [°C]     |
|---|--------------|------|------|------|------|------|------|------|------|------|------|----------|
| Supply water temperature  |              |      |      |      |      |      |      |      |      |      |      |          |
| Maximum cycles feasible in continuous operation                 | <b>27</b>    | 20   | 21   | 23   | 26   | 27   | 27   | 27   | 27   | 27   | 27   | [rack/h] |
| Total spending power from single-skin machine                   | <b>3,02</b>  | 3,03 | 3,03 | 3,03 | 3,02 | 3,02 | 3,02 | 3,02 | 3,02 | 3,02 | 3,10 | [kW]     |
| Total spending power from double-skin machine                   | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |
| Sensible heat emitted into the room from single-skinned machine | <b>0,74</b>  | 0,77 | 0,76 | 0,75 | 0,75 | 0,74 | 0,74 | 0,74 | 0,74 | 0,74 | 0,74 | [kW]     |
| Sensible heat emitted into the room from double-skinned machine | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |
| Latent heat emitted into the room                               | <b>0,37</b>  | 0,18 | 0,20 | 0,24 | 0,27 | 0,30 | 0,32 | 0,34 | 0,35 | 0,37 | 0,39 | [kW]     |
| Emitted standby power with closed door in single-skin machine   | <b>0,33</b>  | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | 0,33 | [kW]     |
| Emitted standby power with closed door in double-skin machine   | -            | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | [kW]     |